

MECHANICAL FEATURES

Device dimensions:	1200 x 600 x h465 mm 47.2 x 23.6 x h18.3 in	Sky-light size:	1086 x 295 mm 42.8 x 11.6 in
Necessary space for installation (largest volume including device, assembled frame, fixing kit):	1200 x 600 x h465 mm 47.2 x 23.6 x h18.3 in	Weight:	30 Kg 66 lb
Fixing kit	The fixing kit includes 4 threaded rods (0.5 m; M6 metric system)		

ELECTRICAL FEATURES

Type of source:	LED
Light output control:	Dimmable by DALI or 0-10V
Light output range:	0.1-100%
Power input:	120V, 60Hz
Max power consumption:	100 W
Typical power consumption:	90 W
Electrical rating	Class II
Power supply units and drivers:	Included

FRAME

Material and Visible dimensions:	HPL, Silver alanod 1200x600xh100 mm / 47.2x23.6xh3.9 in
Weight:	6 kg / 13 lb
Finishing:	White, RAL 9010

DESCRIPTION

Coelux® LS Matte is a recessed ceiling system that artificially reproduces natural light from the sky and the sun. It includes an LED light source, optical components and a Coelux® panel, all housed in a plastic structure. Skylight dimensions: 1086 x 295 mm (42.8 x 11.6 in). Appearance of the sun: visible, slightly frosted. Beam direction: 45°. Appearance of the sky: clear. Frame: included (mandatory for optimal yield), matte. It may also be mounted on normally inflammable surfaces. Inspection hatch: not required.


CERTIFICATIONS

Certifications:	UL, FCC
Certification code:	Coelux LS
Warranty:	2 years

OPTICAL FEATURES

Total Light Output:	3300 lm
Lumen maintenance(L90B10):	> 50000 h
LED CRI (Ra)	> 92
CCT of transmitted beam:	4800 K
CCT of the Sky:	> 30000 K
Photometric diagram (simulated .ies .ldt file, without frame):	Available
Beam angle:	45°
Divergence-FWHM (H/V)(without frames, refer to photometric curves):	13° / 18°
Sun appearance:	Visible slightly frosted
Sky appearance:	Clear
Melanopic Ratio (Sky):	1,577
Melanopic Ratio (Sun):	0,822

PHOTOMETRIC CURVES



OPERATING CONDITIONS

Min/max operating temperature:	-10/40°C
Max operating relative humidity (no condensing):	95%
IP grade:	IP20 (IP44 on the sky panel side only)

SHIPPING INFORMATION

_ No. 3 Carton boxes:
1200x500x650 mm / 47.2x19.7x25.6 in - 32 kg / 70.5 lb and
1250x660x185 mm / 49.2x26.0x7.3 in - 10 kg / 22 lb
Dimensions and weights may differ depending on packaging and shipping conditions.

ACCESSORIES

- 75-00063-01: CBU-A2D - Casambi wireless control unit configured for Coelux LS Classic DALI

- 75-00064-01: CBU-A2D - Casambi wireless control unit configured for Coelux LS Classic 0-10V

NOTES