

ELECTRICAL FEATURES

Type of source:	Tunable white LED
Light output control:	Dimmable by DALI
Light output range:	0.4-100%
Max power consumption:	50 W (3000 K) - 40 W (6500 K)
Power supply units:	Included
Lumen maintenance(L90B10):	> 50000 h

CERTIFICATIONS AND WARRANTY

Certifications:	CE
Warranty:	5 years





OPTICAL FEATURES

Total Light Output:	1600 lm (6500 K)
TUNABLE CCT range:	1800 K - 16000 K
Melanopic Ratio Ultra Warm:	Sky 0.39 / Sun 0.23
Melanopic Ratio Bluish White:	Sky 1.70 / Sun 0.88
LED CRI (Ra):	90
Photometric diagram:	.ies .ldt file available
Beam angle:	Zenith
Divergence (FWTM):	2x30°
CCT of transmitted beam:	4600 K (Noon) / 2600 K (Sunset)
CCT of the Sky:	> 15000 K (Noon) / 4300 K (Sunset)
LED CCT:	6500 K (Noon) / 3000 K (Sunset)
Melanopic Ratio Noon State:	Sky 1.42 / Sun 0.77
Melanopic Ratio Sunset State:	Sky 0.77 / Sun 0.43

MOUNTING INSTRUCTIONS

These assembly instructions must be given to end users for correct maintenance. The appliance must not be tampered with or transformed and it must be installed and used as supplied and in compliance with the National Rules on Installations. Any non-compliant installations will invalidate all forms of guarantee. THE COMPANY CANNOT BE HELD RESPONSIBLE FOR DAMAGE CAUSED BY INCORRECT ASSEMBLY.

MOUNTING SEQUENCE







ATTENTION

Switch-off the power supply before any installation and maintenance operations.

FEATURES AND MEANING OF THE SYMBOLS SHOWN ON THE LABEL:

According to EN 60598-1, EN 60598-2-1

- IP20** Protection against entry of objects larger than Ø 12mm
-  Class II, DOUBLE INSULATION: no earth required
-  Fittings not suitable to be covered with thermal insulation material
-  Do not stare at the operating light source
-  Disposing of as urban waste is forbidden, separate collection is mandatory when the product is at the end of its life
- CE** Product in compliance with the requirements of the European Community Directories

ORDINARY AND EXTRAORDINARY MAINTENANCE

Before performing any routine or extraordinary maintenance on the unit, it is mandatory to disconnect it from the electrical power supply. When cleaning the device, respect the chemical composition of the material, using only cleaners that are compatible with plastics and do not release corrosive substances that could damage the LEDs and electronic components.

ATTENTION

CoeLux S.r.l. disclaims any liability for damage to property, persons, or animals resulting from failure to follow the instructions and warnings provided in this document. If necessary, please contact our company or our sales organization, quoting the purchase order and the serial number of the device. Technical specifications are subject to change without notice!

ACCESSORIES

Accessories that can be ordered separately
 (1x) 27-00035-01: Power Supply 38W - 700mA
 (1x) 75-00076-01 CBU-A2D - Casambi wireless control unit configured for CoeLux System
 75-00057-01: Casambi Xpress - Casambi wireless Keypad user interface - White
 75-00058-01: Casambi Xpress - Casambi wireless Keypad user interface - Black